

# Material Safety Data Sheet U.S. Department of Labor

May be used to comply with  
OSHA's Hazard Communication Standard,  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072



IDENTITY (As Used on Label and List) McCabe Water Level Indicator Paste	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

## Section I

Manufacturer's Name: McCabe and Sons, Inc.	Emergency Telephone Number (603) 694-2102
Address (Number, Street, City, State, and ZIP Code)	Telephone Number for Information (603) 694-2102
2062 Main Rd.	Date Prepared February 17, 1998 Date Revised April 23, 2001
Chatham, NH 03813	Signature of Preparer (optional) <i>Carey A. Wilbur</i>

## Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended % (optional)
Triethanolamine (102-71-6)	---	5 mg/m <sup>3</sup>	
Diethanolamine (111-42-2)	---	2 mg/m <sup>3</sup> (skin)	
Calcium carbonate (1317-65-3)	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable)	10 mg/m <sup>3</sup> (total dust)	
Chromium oxide (1308-38-9)	0.5 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>	

## Section III - Physical/Chemical Characteristics

Boiling Point	Greater than 514 °F	>514 °F	Specific Gravity (H <sub>2</sub> O = 1)	1.7
Vapor Pressure (mm Hg.)	Less than 0.01	Nil	Melting Point	N/A
Vapor Density (AIR = 1)		N/A	Evaporation Rate (Butyl Acetate = 1)	Nil
Solubility in Water	Partial			
Appearance and Odor	Green paste with no odor			

### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) 355-375 °F (COC)	Flammable Limits Not flammable	LEL N/A	UEL N/A
Extinguishing Media Dry chemical, foam, water, or carbon dioxide			
Special Fire Fighting Procedures Dry foam is preferred over water to use to extinguish fires.			
Unusual Fire and Explosion Hazards None			

### Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	None
Incompatibility ( <i>Materials to Avoid</i> ) Avoid contact with acids and oxidizing materials			
Hazardous Decomposition or Byproducts May liberate carbon dioxide, carbon monoxide, and oxides of nitrogen			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	None known

### Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards ( <i>Acute and Chronic</i> ) Acute over exposure can cause irritation of the eyes, respiratory tract, and skin			
Carcinogenicity:	NTP? No	IARC Monographs? Group 3 (Not classifiable)	OSHA Regulated? No
Diethanolamine, Triethanolamine, and Chromium oxide are considered IARC Group 3 chemicals. (Insufficient evidence to classify as an animal or human carcinogens.)			
Signs and Symptoms of Exposure:			
Irritation of the eyes and skin: shortness of breath and reduced pulmonary function in extreme cases.			
Medical Conditions Generally Aggravated by Exposure:			
None known			
Emergency and First Aid Procedures:			

Eye contact: flush with water immediately for 15 minutes. Call a physician  
 Ingestion: Call poison control center and physician immediately.

### Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Segregate and clean up to avoid generating dust and vapors. Consider use of respirators and personal protective equipment in extreme cases involving large quantities of this material.

Waste Disposal Method

Sanitary landfill, incineration at permitted facility

Precautions to Be taken in Handling and Storing

Do not ingest. Avoid contact with eyes and skin. Keep containers closed and away from moisture, acids, and oxidizers. Wash thoroughly after handling. Store in cool, dry, well-ventilated areas. Avoid temperature extremes. A temperature range of 50-75 °F is recommended.

Other Precautions

None

### Section VIII - Control Measures

Respiratory Protection (*Specify Type*)

Consider the use of a NIOSH approved respirator if vapors present above TLV

Ventilation	Local Exhaust Recommended to keep below TLV	Special N/A
	Mechanical ( <i>General</i> ) Recommended	Other Eyewash and safety shower should be available.

Protective Gloves Impervious gloves are usually not required	Eye Protection Safety glasses with side shields, or chemical goggles
---	---

Other Protective Clothing or Equipment

Long sleeved shirt, trousers, safety shoes, rubber gloves and apron

Work/Hygienic Practices

Avoid breathing vapor. Material may be slippery when wet.

**Material Safety Data Sheet**  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements

**U.S. Department of Labor**  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

Identity (As used on Label and List) Kolor Kut Gasoline Gauging Paste © 2.25 oz. jar	Note: Blank spaces are not permitted. If and Item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

**Section I**

Manufacturer's Name Kolor Kut © Products Co., Ltd.	Emergency Telephone Number 713-926-4780
Address (Number, Street City, State and ZIP Code) 7915 East Elm Street Houston, TX 77012	Telephone Number for Information 713-926-4780
Kolor Kut Gasoline Gauging Paste © Kolor Kut © is a registered trademark of Kolor Kut Products Co. Houston, TX	Date February 12, 2015 Signature of Preparer (optional) D. Frauenberger

**Section II – Hazardous Ingredients/Identity Information**

Hazardous Component (Specific Chem. Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
NONE				
All Ingredients Non-Hazardous				

**Section III – Physical / Chemical Characteristics**

Boiling Point	212 Degrees F.	Specific Gravity (H2O=1)	1
Vapor Pressure (mm Hg.)	N/A	Melting Point	120 Degrees F
Vapor Density (AIR=1)	N/A	Evaporation Rate (BUTYL ACETATE=1)	N/A
Solubility in Water Yes			
Appearance and Odor Light Pink Semisolid			

**Section IV – Fire and Explosive Hazard Data**

Flash Point (Method Used) none	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media Standard dry chemical, foam, co-2, water-fog			
Special Fire Fighting Procedures Wear a NIOSH /MSHA approved self contained breathing apparatus and full protective clothing. Cool containers exposed to fire with water.			
Unusual Fire and Explosion Hazards -None-			

**Section V – Reactivity Data**

Stability	Unstable		Conditions to Avoid
	Stable	XXXX	None Known
Incompatibility (Material to Avoid) Oxidizing agents & acids			
Hazardous Decomposition or Byproducts None Known			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	XXXXX	None Known

-1-

Kolor Kut Gasoline Gauging Paste ©  
 Kolor Kut © is a registered trademark of  
 Kolor Kut © Products Company, Ltd.  
 Houston, Texas USA

**Section VI – Health Hazard Data**

Routes(s) of Entry:	Inhalation?	Skin?	Ingestion?
None known at normal temperature.		Mild irritation	
<b>Health Hazards (Acute and Chronic)</b>			
None Known at this time.			
If ingested, induce vomiting immediately by giving 2 glasses of water and sticking finger down throat.			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
This product does not contain any ingredient designated by iarc, ntp, aogh or osha as a known human carcinogen.			
<b>Signs and Symptoms of Exposer</b>			
Irritation and bad odor.			
<b>Medical Conditions Generally Aggravated by Exposure</b>			
Not Determined			
<b>Emergency and First Aid Procedures</b>			
Eyes: use eyewash fountain , get medical attention if irritation develops or persists.			
Skin: use clean cloth – wash w / soap & water. Inhalation- seek medical attention.			
Ingestion: induce vomiting- seek medical attention. Note to physician: treat symptomatically.			

**Section VII – Precautions for Safe Handling and Use**

<b>Steps to Be Taken in Case Material Is Released or Spilled</b>
Unlikely, contain spill, wipe up, and dispose into appropriate container.
<b>Waste Disposal Method</b>
Dispose of in accordance with local , state and federal regulations.
<b>Precautions to Be Taken in Handling and Storing</b>
Store at room temperature do not expose to high temperatures or water contamination.
Don not freeze (for preservation of product only)
Avoid prolonged contact with with skin. Wash hands thoroughly after handling. Do not rub eyes with soiled hands.
<b>Other Precautions</b>
None Known

**Section VIII – Control Measures**

<b>Respiratory Protection (Specific Type)</b>		
No special respiratory protection required.		
Ventilation  NORMAL	Local Exhaust Use local exhaust as needed.	Special Maintain safety equipment.
	Mechanical (General) N/A	Other N/A
Protective Gloves Recommended if desired or as required	Eye Protection safety glasses with side shields.	
Other Protective Clothing or Equipment Work clothing		
<b>Work/Hygienic Practices</b> Be Clean, after applying, clean hands with soap and water.		